



DOG2 MEMS SERIES VOLTAGE INCLINOMETER

SPECIFICATIONS

- ◆ Dual axis inclinometer
- ◆ Measurement ranges $\pm 25^\circ$, $\pm 45^\circ$ and $\pm 90^\circ$
- ◆ Voltage output

FEATURES

- ◆ 8 to 30 VDC supply voltage
- ◆ Digital signal processing includes
 - filter (e.g. vibration damping)
 - temperature compensation
- ◆ 12 bit resolution
- ◆ 100 Hz refresh rate
- ◆ -40°C to 85°C temperature range
- ◆ Accuracy typically
 - 0.5° | -40°C to 85°C
 - 0.15° | 25°C

APPLICATIONS

- ◆ Mobile and stationary cranes
- ◆ Lift platforms
- ◆ Building control
- ◆ Weighing systems
- ◆ Truck chassis leveling
- ◆ Vehicle applications
- ◆ Road construction machines

The **DOG2 MEMS-Series inclinometer** dual axis is mainly developed with focus on platform leveling, dynamic engine management, tip-over protection and tilt alarm.


A fast response time and good accuracy makes this device the ideal choice for mobile leveling applications. It features digital signal processing including temperature compensation.

The integrated filter improves performance and allows using the sensor in many noisy environments (e.g. vibrations).

The inclinometer includes a powerful digital signal processing that offers various filter algorithms and allows customer specific OEM solutions. It is possible to adjust the sensor to different environments yielding an optimized performance. Customization can also be made in terms of angular range and connectivity, i.e. cable and connector.

The PA6.6 housing is very compact in size and has compression limiter bushings for safe installation of the sensor. It is compatible with oil, grease and fuel also. Therefore it is frequently used for engine and vehicle applications.

Dimensions [mm]




PARAMETERS


Parameter	Value	Comment
Range	$\pm 25^\circ$, $\pm 45^\circ$ or $\pm 90^\circ$	Dual axis sensor
Accuracy, typ.	0.5°	T= -40 °C to 85 °C
Accuracy, typ.	0.15°	T= 25 °C
Resolution	12 bit	
Refresh rate	100 Hz	Internal processing
Startup time	<1 s	Valid output signal
Supply/excitation voltage	8 to 30 V	Direct current (DC) stabilized
Supply current, typ.	15 mA	No load
Output	0.5 to 4.5 V	-25° to 25°, -45° to 45° or -90° to 90°
Connector	AMP Superseal 1.5-Series, 4-pos. cap housing, TE Connectivity part-no. 282106-1	Requires 4-pos. plug housing, AMP Superseal 1.5-Series at connecting harness, TE Connectivity part-no. 282088-1
Cable	4 wire 0.25 mm ² , outer diameter Ø3.9 mm	PUR, length incl. connector 400 mm, full temperature range, flexible
Operation temperature range	-40 °C to 85 °C	
Storage temperature range	-40 °C to 85 °C	
Weight, typ.	60 g	
Dimensions	70.5 mm x 45 mm x 15 mm	W x D x H

CONNECTOR PINNING

Pin	Function	Description
1	V _{CC}	8 to 30 VDC supply input (+)
2	GND	GND
3	Output X	0.5 to 4.5 V, X axis output
4	Output Y	0.5 to 4.5 V, Y axis output



TRANSFER CHARACTERISTIC




Part-No.	ϕ_{min}	ϕ_{max}
G-NSDOG2-001	-25°	25°
G-NSDOG2-002	-45°	45°
G-NSDOG2-003	-90°	90°

Linear transfer characteristic between ϕ_{min} and ϕ_{max}

DOG2 MEMS SERIES VOLTAGE INCLINOMETER

FUNCTION VIEW



This DOG2 MEMS series voltage inclinometer is designed for floor mount application.

ORDERING INFORMATION

PART NUMBER	NAME	DESCRIPTION
G-NSDOG2-001	25DOG2 MEMS SERIES VOLTAGE	Dual axis inclinometer, floor mount, range $\pm 25^\circ$, supply 8 to 30 VDC, output voltage 0.5 to 4.5 V
G-NSDOG2-002	45DOG2 MEMS SERIES VOLTAGE	Dual axis inclinometer, floor mount, range $\pm 45^\circ$, supply 8 to 30 VDC, output voltage 0.5 to 4.5 V
G-NSDOG2-003	45DOG2 MEMS SERIES VOLTAGE	Dual axis inclinometer, floor mount, range $\pm 90^\circ$, supply 8 to 30 VDC, output voltage 0.5 to 4.5 V

For other orientations, measurement ranges or supply voltages please contact TE Connectivity sales representatives.